

Spa-N-Deck™ 100% Acrylic Wood Finish



The latest technology acrylic wood finish from Flood that penetrates, protects and outlasts oils 3 to 5 times.



FOR USE ON ALL EXTERIOR WOOD INCLUDING PRESSURE TREATED PINE



- Long lasting and durable
- Proven to withstand severe environments
- Penetrates and protects
- Water based
- Made from 100% of the finest acrylics
- Incorporates the latest UV filters
- Clean and finish the job in one day
- Save time and money



Spa-N-Deck™ 100% Acrylic Wood Finish

Product Description

FloodPro Spa-N-Deck Exterior Wood Finish is a 100% acrylic, premium-quality coating for timber decks, docks and weatherboard cladding. It provides unsurpassed appearance and protection in the most severe ultraviolet environments. It bonds "in" and "on" the wood, providing a tough, durable, lustrous finish that enhances the natural character of the wood.

Basic uses

Exterior wood surfaces
Decks, docks, weatherboards, fences, shingles, pressure-treated pine, plywood, doors, trim and outdoor wood furniture.

Directions

Mix thoroughly before and periodically during application. Once prep steps are completed and thoroughly rinsed, begin application of first coat with the wood wet. **KEEP THE WOOD WET** (especially on decking or horizontal surfaces) during application. Work enough area to maintain a "wet edge" to avoid lapping. The best procedure is to coat one plank at a time from end to end. Allow to dry thoroughly (approximately 1 to 2 hours at 25C) and apply second coat after the first coat is dry. Additional coats are applied to dried finish. Do not rewet after first coat. Inspect the project. If the finish has a uniform sheen and luster, the proper amount of material was applied. If the finish is splotchy or lacks uniformity, apply another coat. Three coats will always give the best results and assure longest durability.

Before you start

Surfaces to be coated must be free of all dirt, grease, grime and previous coatings. Both new and weathered wood must be completely treated with Spa-N-Deck Prep Solution.

New wood surfaces

The ideal time to finish new wood is 1 to 3 months after installation. Some new wood surfaces, like smooth cedar, can have a hard, shiny surface called mill glaze that prevents maximum penetration and bonding of a finish. Mill glaze on new wood should be treated with Spa-N-Deck prep Solution from Flood as per directions.

Weathered wood

Uncoated wood surfaces require thorough cleaning before finishing. Use Spa-N-Deck Prep Solution. Scrub solution into grain with a stiff bristle brush. Follow with pressure washer (minimum 1000 psi) using fresh water or the highest pressure source available.

Previously coated wood surfaces

FloodPro Spa-N-Deck Exterior Wood Finish can only be applied to bare wood surfaces. Remove previous stains, oils or preservatives with Powerlift from Flood. To remove old paint or



varnish use a good stripper such as EzyStrip or environmentally friendly Citristrip, also from Flood. Remove all traces of PowerLift and/or strippers with a pressure washer before using Spa-N-Deck solution and proceeding with Spa-N-deck.

Maintenance

Periodically inspect the finish. If you find small areas that have flaked, cracked or have been damaged from wear and tear, take a scrub brush and brush Spa-N-Deck Prep Solution to affected area - rinse thoroughly and while damp, reapply Spa-N-Deck liberally. Let dry, then apply second coat and feather in.

Coverage

Depends on the application method, surface texture and porosity. Approximate coverage on rough or weathered surfaces: 15 to 25sqm per 4 litre can. On smooth and new surfaces: 35 to 45 sqm per 4 litre can.

Drying time

Apply second coat in 1-2 hours or when dry to touch. Deck can be used in 24-48 hours.

Clean-up

Clean up with warm, soapy water.

Product Characteristics

Finish	Low Luster
Vehicle Type	100% Acrylic
Solvent Type	Water
Wt./Litre	1.03 kg/L
Viscosity	Liquid VOC is 240 g/l
Flammability	NA
Combustibility	NA
Flash Point	greater than 90C
Shelf Life	2 year minimum

Available sizes: 4 litre, 10 litre

For more information and assistance
FREECALL 1800 226 113

THE FLOOD COMPANY AUSTRALIA

4 Nelson Avenue, Padstow, NSW 2211 Australia

Phone (+61) 2 9790 5158 Fax (+61) 2 9709 2604 Email info@floodaustralia.com



MADE IN AUSTRALIA



visit our web site... www.floodaustralia.net