

ESP[®] Easy Surface Prep



Firmly bonds paint to any surface.



Just pour on a clean cloth.



Wipe on surface. Wait 5 minutes and wipe off.



Wait 90 minutes and paint.

- Easy wipe-on, wipe-off application.
- Prepares smooth, slick surfaces for painting or varnishing.
- For use on enamels or varnish, glazed or ceramic tile, baked appliance enamel, lacquer and glass.
- Eliminates time-consuming, labourious sanding.
- Cleans the surface and provides adhesion for oil/alkyd or acrylic paints.
- Unlike deglossers, has a mild,



HOW PAINT SHOULD BE TREATED

ESP[®] Easy Surface Prep

ESP is an easy-to-use, wipe-on, wipe-off liquid that cleans the old surface and leaves a permanent bonding film that promotes strong adhesion of new paint to glossy surfaces. Surfaces prepared with ESP may be repainted after only 90 minutes. (In fact, you can ESP the surface today and recoat even a week later!)

Why use ESP

Old-fashioned de-glossers are harsh and have a strong odour, and sanding is a tough dusty job that most people rush through or avoid. ESP is easy on the hands and has a mild odour. ESP is also easy to use and effective without hard work, so it's a simple task to do the job right the first time- and forget about peeling paint.

How to apply ESP

- Do not thin
- Wipe ESP on the surface, wait 5 minutes, then wipe it off.
- Wait at least 90 minutes before repainting.
- You can even wait up to 7 days before repainting.
- To remove grease or wax buildup, scrub the surface with fine (No.00) steel wool which is saturated with ESP, then wipe off after 5 minutes. Wait at least 90 minutes before repainting.
- If the new paint 'crawls' or separates, the surface is not really clean. Wipe off the wet paint and reclean the surface with detergent and water. Allow the surface to dry thoroughly and try the paint again.



Coverage, clean up and storage

- 1/2 litre of ESP will prepare surface for 4 litres of paint.
- Clean up with mineral spirits.
- Keep container tightly sealed when not in use.

Available Sizes:

500 ml, 1 litre, 4 litre.

For more information and assistance

FREECALL 1800 226 113

THE FLOOD COMPANY AUSTRALIA

4 Nelson Avenue, Padstow, NSW 2211 Australia

Phone (+61) 2 9790 5158 Fax (+61) 2 9709 2604 Email info@floodaustralia.com

visit our web site... www.floodaustralia.net



MADE IN AUSTRALIA



HOW PAINT SHOULD BE TREATED