



THE FLOOD COMPANY AUSTRALIA PTY LTD

ABN 92 003 024 600

4 Nelson Ave, Padstow NSW 2211

Ph 02 9790 5158 Fax 02 9709 2604

E-Mail: [info@floodaustralia.com](mailto:info@floodaustralia.com)

Web Site: [www.floodaustralia.net](http://www.floodaustralia.net)

# ALUMINIUM PENETROL FACT SHEET

## **Description**

*Penetrol Aluminium* is a combination of proven *Penetrol* and high-grade aluminium paste, resulting in a bright metallic aluminium coating. Originally designed for the protection of cargo holds it has very high anti-corrosion properties as well as light reflecting ability, which will help to lower temperatures under metal roofing.

## **Purpose**

*Penetrol Aluminium* provides low cost rust/corrosion protection and restores an acceptable appearance for wire fencing, utility towers and light poles, galvanised roofs, metal structures and storage tanks.

## **Drying Time**

*Penetrol Aluminium* is touch dry in 4 - 6 hours.

## **Container Size**

*Penetrol Aluminium* is available in 1, 4, and 10 litre containers.

## **Application**

Apply *Penetrol Aluminium* by brush, roller, or spray.

## **Coverage**

*Penetrol Aluminium* will cover 10 -12 sq mtr per litre.

## **Clean-up**

Clean brushes and spills with mineral turpentine.

## **Safety Directions**

If swallowed, do not induce vomiting. Call physician immediately. Avoid prolonged contact with skin and breathing of vapours or spray mist. Wear goggles with side shields when spraying. If in eyes or on skin, wash with copious amounts of water and seek medical attention if irritation persists.

## **Waste Disposal**

Used rags saturated with *Penetrol Aluminium* may be subject to spontaneous combustion when discarded. Always unfold and allow rags to dry before disposal in accordance with local regulations.