



THE FLOOD COMPANY AUSTRALIA PTY LTD

ABN 92 003 024 600

4 Nelson Ave, Padstow NSW 2211

Ph 02 9790 5158 Fax 02 9709 2604

E-Mail: info@floodaustralia.com

Web Site: www.floodaustralia.net

PENETROL WOOD OIL FACT SHEET

Description

Penetrol Wood Oil is an air-drying, film forming, deeply penetrating blend of natural oils which replaces the natural oils lost in wood. It does not contain linseed or fish oil, has a low odour and is non-toxic when dry. With a penetrating power 3 times that of water it goes deep into the wood. It will not yellow and never peel, crack or blister.

Purpose

To enhance and protect the natural beauty of fine wood and prevent water ingress. To prevent cracks and rejuvenate dull old wood. To be used under varnish for better adhesion. To make beautiful and long lasting stains. Ideal for D.I.Y projects.

Application

Apply *Penetrol Wood Oil* by brush, roller or lint free cloth.

Drying Time

4 - 12 hours

Container Size

Penetrol Wood Oil is available in 300g aerosol, 500ml, 1, 4, and 20 litre containers. Also in 500ml and 1litre base packs for easy in-store tinting.

Coverage

Penetrol Wood Oil will cover from 4 -12 sq meters per litre depending on surface porosity. On old timber coverage may be as low as 2 sq metres per litre.

Clean-up

Clean equipment and spills with mineral turpentine. Remove dried spatter or spills with a suitable paint remover. Always check for surface compatibility first.

Safety Directions

Follow common sense painting procedures. Wear protective glasses and gloves. If in eyes or on skin, wash with copious amounts of water and seek medical attention if irritation persists.

Waste Disposal

Used rags saturated with *Penetrol Wood Oil* may be subject to spontaneous combustion when discarded. Always unfold and allow rags to dry before disposal in accordance with local regulations.