



THE FLOOD COMPANY AUSTRALIA PTY LTD

ABN 92 003 024 600

4 Nelson Ave, Padstow NSW 2211

Ph 02 9790 5158 Fax 02 9709 2604

E-Mail: info@floodaustralia.com

Web Site: www.floodaustralia.net

CWF-UV FACT SHEET

Description

CWF-UV is a clear penetrating exterior timber finish made from a blend of natural oils and resins in an environmentally friendly oil/water emulsion. It is available in natural clear as well as a transparent Cedar tone. It is designed for use on weathered wood and not suitable for new timber.

Purpose

To restore weathered wood to a rich natural appearance; to protect wood from excessive moisture absorption; to resist attack from ultraviolet light, fungus and mildew; to allow for easy and long-term maintenance.

Application

Clean first with *Dekswood Timber Cleaner* before coating with *CWF-UV* by brush, roller or spray. Two to three coats and always wet on wet.

Drying Time

Touch dry in 4 hours. 20 minutes between coats.

Container Size

CWF-UV is available in 4 and 20 litres containers.

Coverage

Rough sawn timber: 5 - 8 square metres per litre

Dressed Timber: 8 -10 square metres per litre

Coverage will increase with each coat.

Clean-up

Clean equipment and spills with mineral turpentine. Remove dried spatter or spills with a suitable paint remover. Always check for surface compatibility first. Protect areas not to be coated.

Safety Directions

Clean equipment and spills with mineral turpentine. Remove dried spatter or spills with a suitable paint remover. Always check for surface compatibility first. Protect areas not to be coated.

Waste Disposal

Used rags saturated with *CWF-UV* may be subject to spontaneous combustion when discarded. Always unfold and allow rags to dry before disposal in accordance with local regulations.