



THE FLOOD COMPANY AUSTRALIA PTY LTD

ABN 92 003 024 600

4 Nelson Ave, Padstow NSW 2211

Ph 02 9790 5158 Fax 02 9709 2604

E-Mail: info@floodaustralia.com

Web Site: www.floodaustralia.net

CWF Clear Wood Finish FACT SHEET

Description

CWF Clear Wood Finish is a clear penetrating exterior timber finish made from a blend of natural oils and resins. It is available in natural clear as well as a transparent Cedar tone. It is designed for use on weathered wood and not suitable for new timber.

Purpose

To restore weathered wood to a rich natural appearance; to protect wood from excessive moisture absorption; to resist attack from ultraviolet light, fungus and mildew; to allow for easy and long-term maintenance; for people who prefer a traditional all oil finish.

Drying Time

Touch dry in 4 hours. 20 minutes between coats.

Container Size

CWF Clear Wood Finish is available in 1, 4, and 20 litres containers.

Application

Clean first with *Dekswood Timber Cleaner* before coating with *CWF Clear Wood Finish* by brush, roller or spray. Two to three coats and always wet on wet.

Coverage

Rough sawn timber: 5 - 8 square metres per litre

Dressed Timber: 8 -10 square metres per litre.

Coverage will increase with each coat.

Clean-up

Clean equipment and spills with mineral turpentine. Remove dried spatter or spills with a suitable paint remover. Always check for surface compatibility first. Protect areas not to be coated.

Safety Directions

Follow common sense painting procedures. Wear protective glasses and gloves. If in eyes or on skin, wash with copious amounts of water and seek medical attention if irritation persists.

Waste Disposal

Used rags saturated with *CWF Clear Wood Finish* may be subject to spontaneous combustion when discarded. Always unfold and allow rags to dry before disposal in accordance with local regulations.