

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 March 2008

Product Name: Deks OLJE 1

STATEMENT OF HAZARDOUS NATURE:

HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

Section 1 - Identification of the Material and Supplier

COMPANY DETAILS: The Flood Company Australia P/L
 ACN 92 003 024 600
 4 Nelson Avenue Padstow NSW 2211
 Ph: 02 9790 5158, 1800 226-113
 Fax: 02 9709-2604
 A/H 02 9826-6929

PRODUCT:

Product Name: Deks Olje #1
Other Names: Not Applicable
Manufacturer's Product Code: 9 314177 1400XX (XX is package size)

Use: Wood finish

Section 2 - Hazards Identification

This product is not a dangerous good
 UN Number: Not Applicable
 Dangerous Goods Class and Subsidiary Risk: DOT class not regulated. Not a dangerous good according to the Australian Dangerous Goods Code
 Hazchem Code: Not Applicable
 Poisons Schedule Number: Not applicable

Section 3 - Composition/Information on Ingredients

Naphta - Hydrotreated petroleum C9-C16 CAS No 64742-47-8	65 -80 %
Hydrocarbons	

Section 4 First Aid Measures

Swallowed: Rinse mouth, then drink 1 or 2 large glasses of water, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Get Medical attention.

Eye: Flush immediately with plenty of cool running water. Remove contact lenses continue flushing for 15 minutes. If irritation persists get medical attention

Skin: Flush skin with cool running water. Wash thoroughly with soap and water. Contaminated clothing should be removed, and cleaned before reuse. Never apply solvents for cleaning the skin. Apply a hand cream if skin is dried out.

Inhaled: Using respiratory protection. Immediately remove to fresh air if needed. Administer artificial respiration /CPR as appropriate if breathing stopped. Seek medical attention.

IF IRRITATION PERSISTS CALL A DOCTOR

Advice to Doctor: Treat symptomatically

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 March 2008

Product Name: Deks OLJE 1

Section 5 Fire Fighting Measures

Use water spray to cool fire exposed surfaces and to protect personnel. Shut of fuel to fire if safe to do so. Use foam, dry chemical or water spray to extinguish fire. Use adequate personal protection, including respiratory protection or self-contained breathing apparatus. Avoid spraying water directly on burning product, Avoid spills of polluted water to sewer or aquatic environment.

Product is combustible and ignitable at temperatures over the flashpoint. Vapours heavier than air may spread along the ground to ignition sources, or accumulate on low places with explosion and ignition hazard. Spray fog is highly flammable. Drying oils may ignite spontaneously with combustible materials such as rags.

Section 6 Accidental Release Measures

Land Spill:

Keep public away. Shut off source if possible to do so and safe. Advise authorities if substance has entered a water way or sewer or contaminated soil or vegetation.

Contain with inert substance such as earth or sand

Ventilate area. Use reparatory protection and protective clothing. Observe potential for slippery floor.

Petroleum based or emulsifying degreaser may be used for cleaning.

Remove all sources of vapour ignitions.

Small Spill: Remove liquid by oil-absorbing materials.

Section 7 Handling and Storage

Store in tightly closed original containers in a cool and ventilated place. Keep away from children. Combustible. Prevent contact with flames or hot surfaces. Do not store near heat. Avoid prolonged contact with skin. Avoid breathing concentrated vapors. Store out of sun and away from heat. Conditions To Avoid: Storage of combustible materials wetted with liquid can produce heat and spontaneous combustion.

Section 8 Exposure Controls/Personal Protection

Exposure limits: Naphta (Petroleum) TWA: 1200 mg/m³ (171ppm)

Ventilation: The use of mechanical ventilation is recommended to maintain levels below recommended thresholds.

Respiratory Protection: Normally not necessary. If there is a risk of inhalation of vapors a suitable respirator Gasmask with filter A for organic materials is recommended..

Protective Gloves: Oil resistant gloves if prolonged liquid contact is likely.

Eye Protection: Goggles with side shields

Other Protective Clothing: Oil repellent, protective clothing if prolonged liquid contact is likely.

Hygienic Practices: Wash hands with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse.

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 March 2008

Product Name: Deks OLJE 1

Section 9 Physical and Chemical Properties

Appearance: Clear amber oil
Boiling Point: >150°C
Vapour Pressure: <0.1kPa (at 20°C)
Specific Gravity: 0.87g/cm³
Solubility in Water: Insoluble
Vapour Density: >1
Viscosity: >7 mm²/s at 40°C
Explosion Limits: 0.6 – 8.0 Vol %
Auto Ignition Temperature: >200°C

Section 10 Stability and Reactivity

Stable under normal conditions
Hazardous Polymerisation: Will not occur

Section 11 Toxicological Information

Swallowing: Can cause irritation of mucous membranes, abdominal pain, nausea, vomiting and diarrhea. Vomiting may cause bronchopneumonia or pulmonary odema.
May result from vomiting.

Eye: May cause redness and slight irritation.

Skin: Brief skin contact is considered harmless. Frequent and repeated contact can cause drying of the skin and incidental irritation.

Inhalation: Repeated or frequent inhalation of vapour or spray fog will irritate the respiratory tract
May cause dizziness and headache. Could be anesthetic and have other central nervous system effects.

Section 12 Ecological Information

May be toxic to aquatic organism, may cause long term adverse effects in the aquatic environment. Do not allow product to enter drains, waterways or sewers.
Volatile ingredients will rapidly evaporate to the air if released into the water.

Section 13 Disposal Considerations

Dispose in accordance with local authority in an approved waste disposal location.
Dispose of in accordance with applicable pollution control regulations. Rags, paper and other combustible material soiled with drying oil should be kept in a safe place, wetted with water to avoid possible spontaneous ignition.

Section 14 Transport Information

This product is not a dangerous good for transport

UN Number: Not applicable

UN Proper Shipping Name: Not applicable

Class and subsidiary risk(s): Not applicable

Hazchem Code: Not applicable

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 March 2008

Product Name: Deks OLJE 1

Section 15 Regulatory Information

Classified as hazardous substance to criteria of NOHSC

Section 16 Other Information

Keep out of reach of children.

The above information is believed to be correct with respect to the formula used in manufacture of the product. As data, standards and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY. EXPRESSED OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION