

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 April 2008

Product Name: ESP Easy Surface Prep

STATEMENT OF HAZARDOUS NATURE:

HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

Section 1 - Identification of the Material and Supplier

COMPANY DETAILS: The Flood Company Australia P/L

ACN 92 003 024 600

4 Nelson Avenue Padstow NSW 2211

Ph: 02 9790 5158, 1800 226-113

Fax: 02 9709-2604

A/H 02 9826-6929

PRODUCT:

Product Name: ESP Easy Surface Prep**Other Names:****Manufacturer's Product Code:** 9 314177 2000XX (XX is package size)**Use:** Preparation of non-porous surfaces before painting

Section 2 - Hazards Identification

HAZARDOUS SUBSTANCE – According to NOHSC- DANGEROUS GOOD

Dangerous good class 3 Flammable

Section 3 - Composition/Information on Ingredients

INGREDIENT	PERCENT	OCCUPATIONAL EXPOSURE LIMIT TLV PEL	VAPOR PRESSURE	LD50 ORALRAT	LC50 IHL - RAT
Petroleum Distillates: A blend of CAS # 64742- 88-7, and #64742-95-6	90 80-90% <5%	100ppm 100ppm 100ppm 100ppm	<7mm Hg @ 38°C	N/A	Not Available
Mineral Spirits CAS #8052- 41-3	1-5%	100ppm 100ppm	Not Available	N/A	Not Available
1,2,4 - Trimethyl Benzene CAS #95-63-6	<2	25 25	Not Applicable	5g/kg	18g/M3/4Hrs

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 April 2008

Product Name: ESP Easy Surface Prep

Section 4 First Aid Measures

SKIN: Wash affected area with soap and water, flush with large amounts of water. If irritation persists, get medical attention. Do not continue to wear oil-soaked clothing.

Discard oil-soaked leather goods.

EYE: Flush immediately with large amounts of water for at least 15 minutes while holding eyelids open. Get medical attention.

INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist.

SWALLOWING: DO NOT INDUCE VOMITING DUE to danger of aspirating oil into the lungs. If vomiting occurs spontaneously, keep head below hips to prevent breathing of liquid into the lungs. DO NOT give anything by mouth if the person is unconscious or having convulsions. Get medical attention immediately.

NOTES TO PHYSICIAN: Aspiration of liquid petroleum products into lungs may cause severe pneumonitis (oil pneumonia). Vomiting should not be induced.

Section 5 Fire Fighting Measures

FLASH POINT: 44° C. T.C.C.
 LEL: NOT ESTABLISHED
 EXTINGUISHING MEDIA: (X) FOAM () ALCOHOL FOAM (X) CO2 (X) DRY
 CHEMICAL (X) WATER FOG () OTHER
 UPPER FLAMMABLE LIMIT: NOT AVAILABLE
 LOWER FLAMMABLE LIMIT: NOT AVAILABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible. Exposure of closed containers to heat can cause disruptive pressure. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Do not flush into public sewer system.

SPECIAL FIREFIGHTING PROCEDURES: Water may be ineffective as extinguishing medium but may be used to cool closed containers exposed to heat. Respiratory protection should be self-contained, breathing apparatus type with a full face piece operated in a pressure demand or other positive pressure mode.

Section 6 Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of vapor ignitions. Ventilate area and stop spill at source. **SMALL SPILL:** Remove liquid with oil-absorbing materials. **LARGE SPILL:** Exclude persons not wearing protective equipment, dike area of spill and pump liquid into salvage tank.

Section 7 Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: COMBUSTIBLE. Prevent contact with flames or hot surfaces. Do not store near heat. Keep containers closed when not in use. Avoid prolonged contact with skin. Avoid breathing concentrated vapors.

OTHER PRECAUTIONS: Store only in well-ventilated areas. Store out of sun and away from heat.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 April 2008

Product Name: ESP Easy Surface Prep

Section 8 Exposure Controls/Personal Protection

RESPIRATORY PROTECTION: If TLV of the product or any component is exceeded, a NIOSH/OSHA jointly approved, air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/OSHA respirators under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

PROTECTIVE GLOVES: Oil resistant if prolonged contact is likely.

EYE PROTECTION: Goggles with side shields when spraying or where splashing is likely.

OTHER PROTECTIVE EQUIPMENT: Oil repellent, protective clothing if prolonged contact is likely.

HYGIENIC PRACTICES: Wash hands with soap and water thoroughly after use. Launder contaminated clothing before reuse.

Section 9 Physical and Chemical Properties

BOILING RANGE	163-201 DEGREES C.
VAPOR DENSITY	HEAVIER THAN AIR
EVAPORATION RATE	SLOWER THAN ETHER
VOLATILE VOLUME	92%
DENSITY	0.79 Kg/ L
PHYSICAL STATE LIQUID	APPEARANCE & ODOR PALE YELLOW, MILD SOLVENT ODOR
ODOR THRESHOLD	NOT AVAILABLE
FREEZING POINT	NOT APPLICABLE
Flashpoint:	>40°C (TCC)
Flammability Limits:	Not Available
Lower Flammable Limit:	Not Available

Section 10 Stability and Reactivity

STABILITY: (X) STABLE

HAZARDOUS POLYMERIZATION: (X) WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion in restricted environments may produce carbon monoxide, carbon dioxide and various hydrocarbons.

CONDITIONS TO AVOID: Contact with heat, flames or strong oxidizing agents.

Storage of combustible materials wetted with liquid can produce heat and spontaneous combustion.

INCOMPATIBILITY (MATERIALS TO AVOID): Stable under normal conditions of use.

Avoid contact with strong oxidizers.

Section 11 Toxicological Information

EFFECTS OF OVEREXPOSURE:

SKIN: May cause skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in dermatitis.

EYE: May cause eye irritation. Symptoms include stinging, tearing, redness.

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 April 2008

Product Name: ESP Easy Surface Prep

INHALATION: Vapors may cause narcosis and irritation of respiratory system. Prolonged or repeated contact can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

SWALLOWING: Can cause gastrointestinal irritation, vomiting. Aspiration (breathing) of vomitus into lungs must be avoided; can enter lungs and cause severe damage. Harmful or fatal if swallowed.

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product.

PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL (X) INHALATION (X) INGESTION (X) EYE

Section 12 Ecological Information

The volatile component will rapidly evaporate to the air if released into the water. This component is "Readily" biodegradable according to OECD guidelines. May be toxic to aquatic organisms.

Environmental protection: Do not allow to enter drains, waterways or sewers

Section 13 Disposal Considerations

WASTE DISPOSAL METHOD: Do not incinerate closed containers. Do not dispose of waste material in sewers or waterways. Promptly incinerate wetted, combustible, oil absorbing materials. Dispose in accordance with all local, State and Federal regulations.

Section 14 Transport Information

This product is a class 3 dangerous good for transport

UN Number: 1273

UN Proper Shipping Name: Paint and related products

Class and subsidiary risk(s): Not applicable

Hazchem Code: 3W

DOT - COMBUSTIBLE LIQUID

Not regulated by ground transportation in non-bulk packaging (450 L or 119 gallons or less) per 49 CFR 173.150 (f)(2).

Section 15 Regulatory Information

UN Number: 1263

Dangerous Goods Class and Subsidiary Risk: Class 3 according to the Australian Dangerous Goods Code

Hazchem Code: Not Applicable

Poisons Schedule Number: Not applicable

US SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS# Chemical Name % by Weight 95-63-6 1,2,4 - Trimethyl Benzene <2

MATERIAL SAFETY DATA SHEET

Date of Issue: 25 April 2008

Product Name: ESP Easy Surface Prep

Section 16 Other Information

Keep out of reach of children.

Reference information is taken from the American version of this MSDS.

The above information is believed to be correct with respect to the formula used in manufacture of the product. As data, standards and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY. EXPRESSED OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION