



## Material Safety Data Sheet

August 2004

# SPA-N-DECK White & Driftwood Grey

Page 1 of 3

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the Occupational Safety and Health Administration (OSHA).

**DESCRIPTION:** Acrylic Exterior Wood Finish

**MANUFACTURER:** The Flood Company Australia P/L  
4 Nelson Ave, Padstow NSW 2211  
Ph: 02 9790 5158, 1800 226-113  
A/H 02 9826 6929

### PRODUCT IDENTIFICATION

|                        |                                    |
|------------------------|------------------------------------|
| Label Name:            | SPA-N-DECK – White, Driftwood Grey |
| Other Names:           | none                               |
| UN Number:             | Not applicable                     |
| Dangerous Goods Class: | Not applicable                     |
| Hazchem Code:          | Not applicable                     |
| Poisons Schedule:      | Not applicable                     |

### PHYSICAL DESCRIPTION/PROPERTIES

|                      |                           |
|----------------------|---------------------------|
| Appearance:          | White or grey, mild odour |
| Boiling Range:       | 79°C                      |
| Flashpoint:          | 79°C                      |
| Solubility in Water: | Soluble                   |
| Odour Threshold:     | not available             |
| Freezing Point:      | 1°C                       |

### OTHER PROPERTIES

|                                   |   |
|-----------------------------------|---|
| Evaporation Rate:                 | Slower than Ether   |
| Vapour Density:                   | Lighter than Air  |
| Volatile Volume:                  | 86.8%   |
| Weight/Litre:                     | 4 kg/4 litres   |
| Reactivity:                       | Stable  |
| Viscosity:                        | .20 poises at 25°C  |
| Stability:                        | Stable  |
| pH:                               | 8.5 - 9.5   |
| Hazardous Polymerisation:         | Will not occur  |
| Hazardous Decomposition Products: | Thermal decomposition may generate carbon monoxide and carbon dioxide |

**HAZARDOUS INGREDIENTS**

| <b>Chemical Name</b>                                    | <b>CAS Number</b> | <b>% Weight</b> |
|---|-------------------|-----------------|
| 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate Texanol | 25265-77-4        | < 5             |
| Titanium Dioxide  | 134-67-7          | < 5             |
| 1,2,-Propanediol Propylene Glycol                       | 57-55-6           | < 5             |
| Water/Inerts/Acrylic Polymer                            | n/a               | > 75            |

**HEALTH HAZARD INFORMATION**

**PRIMARY ROUTE(S) OF ENTRY**    ✓ Dermal    ✓ Ingestion    ✓ Eye

**HEALTH EFFECTS**

Ingestion: Swallowing large amounts may cause abdominal discomfort, nausea, vomiting.  
Eye: May cause mild eye irritation or discomfort.  
Skin: May cause mild skin irritation or discomfort.  
Inhalation: Short-term harmful effects are not expected from vapour. Prolonged exposure may lead to mild and temporary respiratory irritation.

**FIRST AID**

Swallowing: If large amounts are swallowed or if irritation occurs, seek medical attention. Drink one or two glasses of water. Do not induce vomiting or give anything by mouth to an unconscious person.  
Eye: Flush immediately with large amounts of clean cool water for at least 15 Minutes. If irritation persists, get medical attention.  
Skin: Wash affected area with soap and water, flush with large amounts of water.  
Inhaled: Remove to fresh air. Seek medical attention if symptoms persist.

**PRECAUTIONS FOR USE**

**RESPIRATORY PROTECTION**

None needed under normal conditions. If spray applying and/or vapours, mists or aerosols are generated, additional protection may be obtained by wearing a NIOSH/MSHA approved respirator.

**VENTILATION**

Use with adequate ventilation.

**PROTECTIVE GLOVES**

Impervious gloves, to minimize contact.

**EYE PROTECTION**

Goggles with side shields when spraying or where splashing is likely.

**OTHER PROTECTIVE CLOTHING**

None needed with normal use.

**HYGIENIC PRACTICES**

Wash hands with soap and water before eating, drinking, smoking, or using toilet facilities.

|                                  |
|----------------------------------|
| <b>SAFE HANDLING INFORMATION</b> |
|----------------------------------|

Keep container closed when not in use. Store at room temperature, maximum recommended is 49°C. Do not freeze or store near source of heat.

**SPILLS AND LEAKAGE**

Contain spill and pick up with absorbent material.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with applicable pollution control regulations.

**FIRE HAZARD**

Not applicable

**EXTINGUISHING MEDIA**

Foam ✓      CO2 ✓      Dry Chemical ✓      Water Fog ✓      Alcohol Foam      Other

**FIRE FIGHTING PROCEDURES**

Normal fire fighting procedures may be used. Wear self-contained breathing apparatus and full protective gear. Closed containers may burst if exposed to extreme heat or fire.

**MANUFACTURER:**      The Flood Company Australia P/L  
4 Nelson Ave, Padstow NSW 2211  
Ph: 02 9790 5158, 1800 226-113  
A/H 02 9826 6929